

**Product Data** 

# Driwall<sup>™</sup> Rainscreen UV 6mm (1/4")

A High Performance Drainage and Ventilation Mat for Exposed Joint Cladding

### Description

Driwall Rainscreen UV is a 0.20 (1/4) inch-thick, randomly oriented geometric patterned high performance drainage and ventilation mat.

It is designed to provide a 0.20 (1/4) cavity with a long term UV resistance. Driwall Rainscreen UV has strength bars to increase compression resistance and with the addition of a UV stable fabric it makes Driwall Rainscreen UV ideal for open joint claddings.

The UV stable fabric is black in color to contrast the emptiness and the entangled net is designed to deter insect and rodents from resting.

Open joint cladding limitation maximum open gap 3/8-inch, minimum cladding thickness of 3/8-inch.

## Applications

- Fiber cement board siding
- Wood siding
- Open joint cladding
- ✓ Metal panels

## **Features and Benefits**

Drainage of excess moisture and ventilation in one product

Light weight and easy to handle

Simple installation with mechanical staple hammer


Polymer core is resistant to most known corrosive chemicals, including solvents

Wide rolls for fewer seams

Core ABSORBS and RELEASES NO MOISTURE

Provides no source for the promotion of MOLD, MILDEW or BACTERIA

Driwall Raisncreen products have ASTM 2273 approval



#### **Physical Properties**

Description	Means of Measurement English/Metric		Value English/Metric		
Flame Spread	ASTM E84		Class A		
Core Polymer	Polypropylene, UV-Stabilized				
Thickness	Inches	Mm	0.25	6.3	
Total Weight	oz/yd <sup>2</sup>	g/m <sup>2</sup>	12.7	403.6	
Core Weight	oz/yd <sup>2</sup>	g/m <sup>2</sup>	10.8	366.2	
Fabric Weight	oz/yd <sup>2</sup>	g/m <sup>2</sup>	1.9	64.0	

#### Packaging

Description	Means of Measurement English/Metric		Value English/Metric	
Core Width	Inches	СМ	48.0	122
Length	Feet	Meters	65.0	19.8
Area	Square Feet	Square Meters	260	24.2
Roll Diameter	Inches	СМ	16.0	40.6
Roll Weight	Pounds	Kg	19.5	8.8

#### See installation instructions for methods and procedures.

25 YEAR LIMITED WARRANTY

KEENE BUILDING PRODUCTS, INC. DRIWALL RAINSCREEN

Keene Building Products, Inc. ("Keene") warrants its DRIWALL RAINSCREEN products against defects in material and workmanship for a period of Twenty-Five (25) years from the date of installation. Upon receipt of written notice, which must be given no later than thirty (30) days after discovery of the defect, Keene, at its sole option, will repair or replace the defective items(s) or refund the purchase price. Keene, at its sole option, may request that the defective item(s) be returned to Keene's principal offices for investigation and inspection. Keene is not required to repair or replace the defective item(s) that Keene has requested returned and has inspected such item(s).

The warranty provided above is extended solely to the person or entity that purchases the product directly from Keene, and no third party may rely thereon or assert any claim based on such warranty. The foregoing warranty is the only warranty provided by Keene and is to the exclusion of any other warranty, whether express or implied, including the implied warranties of merchantability and fitness for a particular purpose, all of which are expressly disclaimed. Keene's liability, if any, for damages based on any claim of any kind whatsoever, and regardless of the legal theory, with regard to any of its products shall be limited to the actual purchase price of the product(s) with respect to which such claim is made. UNDER NO CIRCUMSTANCES SHALL KEENE BE LIABLE TO PURCHASER FOR COMPENSATION, REIMBURSEMENT OR DAMAGES ON ACCOUNT OF

UNDER NO CIRCUMSTANCES SHALL KEENE BE LIABLE TO PURCHASER FOR COMPENSATION, REIMBURSEMENT OR DAMAGES ON ACCOUNT OF THE LOSS OF PRESENT OR PROSPECTIVE PROFITS OR REVENUE, EXPENDITURES, INVESTMENTS OR COMMITMENTS, AND IN NO EVENT SHALL KEENE BE LIABLE TO PURCHASER OR ANY OTHER PERSON OR ENTITY FOR SPECIAL, INCIDENTAL, INDIRECT, CONSEQUENTIAL OR EXEMPLARY DAMAGES. By way of example only, Keene will not be responsible for any damages purchaser may incur that are related to surface, subsurface or building conditions, damage to the structure or contents of any building, or for costs of repair and replacement except as may be expressly provided in this Limited Warranty (and subject to the terms and conditions hereof).

Keene shall not be liable for product failure resulting from any of the following: (i) products not installed in accordance with Keene's installation instructions; (ii) noncompliance with applicable building codes and regulations; (iii) the use of any of its products (A) in a manner for which it was not intended; (B) in a modified form without the permission of Keene, or (C) in combination with any other system, equipment or device not manufactured or sold by Keene.

Keene may change, modify, amend, replace or discontinue offering a product warranty, limited or otherwise. Any such change, modification, amendment, replacement or discontinuance shall be applicable to unsold products only, and Keene shall endeavor to give purchaser at least thirty (30) days prior written notice of same. Claims or inquiries shall be addressed as follows:

Customer Service Department [Quality Control Manager] KEENE BUILDING PRODUCTS, INC. 2926 Chester Avenue Cleveland, OH 44114 P 440 605 1020 [877-514-5336] F 440 605 1120 www.keenebuilding.com



P.O. Box 241353 Mayfield Heights, OH 44124 Info@KeeneBuilding.com KeeneBuilding.com

877 | 514 | 5336 P 440 | 605 | 1020 2/2 F 440 | 605 | 1120 2020/12